Docket No.: M4065.0433/P433

AMENDMENTS TO THE CLAIMS

Claim 1. (currently amended): A circuit having support for normalization of significants, significants, comprising:

a first register block, said first register block including at least one first register for holding a first exponent and a first <u>significant</u> significand of a first floating point number and a first logic capable of left shifting the <u>significant</u> significand of the first floating point number;

a second register block, said second register block including at least one second register for holding a second exponent and a second <u>significant</u> of a second floating point number;

a plurality of flags, coupled to said first register block, each of said plurality of flags having a state based on the contents of said first significant; significand;

an arithmetic logic unit coupled to said first register block, said second register block, and said plurality of flags, said arithmetic logic unit causing the first logic to left shift the first significant significand based upon the states of said plurality of flags.

Claim 2. (currently amended): The circuit of claim 1, wherein said plurality of flags further comprises:

an Ith flag, wherein I is a non-negative integer, said Ith flag which is set to a first sate when the 2^I most significant bits of said first <u>significant</u> are each zeros and a second state if any of the 2^I most significant bits is non-zero.

Docket No.: M4065.0433/P433

Claim 3. (currently amended): The circuit of claim 2, wherein said arithmetic logic unit causes said first logic to left shift by 21 bits the first significant significand if said Ith flag

is set to the first state.

Claim 4. (original): The circuit of claim 3, wherein said arithmetic logic unit is coupled to a temporary storage location for storing an adjustment to be subtracted from said first exponent, and increments said adjustment by 21 if said first flag is set to the first

state.

Claim 5. (original): The circuit of claim 2, wherein I is 0.

Claim 6. (original): The circuit of claim 2, wherein I is 1.

Claim 7. (original): The circuit of claim 2, wherein I is 2.

Claim 8. (original): The circuit of claim 2, wherein I is 3.

4

Claim 9. (original): The circuit of claim 1, wherein said arithmetic logic unit is coupled

Docket No.: M4065.0433/P433

to a temporary storage location.

Claim 10. (original): The circuit of claim 9, wherein said temporary storage location is a register in a register file.

Claim 11. (original): The circuit of claim 9, wherein said temporary storage location is a main memory accessed through a memory interface.

 $\mathcal{I}_{/}$

Claim 12. (currently amended): The circuit of claim 1, wherein:

said plurality of flags further comprises,

an Ith flag, wherein I is a positive integer of at least 3, which is set to a first state when the 2^I most significant bits of said first <u>significant</u> are each zeros and a second state if any of the 2^I most significant bits of said first <u>significant</u> is non-zero;

an (I-1)th flag which is set to a first state when the 2^(I-1) most significant bits of said first significant significand are each zeros and a second state if any of the 2^(I-1) most significant bits of said first significant significand is non-zero;

an (I-2)th flag which is set to a first state when the 2^(I-2) most significant bits of said first significant significand are each zeros and a second state if any of the 2^(I-2) most significant bits of said first significant significand is non-zero; and

Docket No.: M4065.0433/P433

an (I-3)th flag which is set to a first state when the 2^(I-3)significant bits of said first significant significand are each zeros and a second state if the 2^(I-3) significant bits of said first significant significand is non-zero; and wherein

said arithmetic logic unit is coupled to a temporary storage location, said arithmetic logic unit initially setting the temporary storage location to zero, then modifying said temporary location based upon the state of the plurality of flags, and finally modifying said first exponent based on the contents of said temporary location.

Claim 13. (original): The circuit of claim 12, wherein said temporary storage location is a register in a register file.

() /

Claim 14. (original): The circuit of claim 12, wherein said temporary storage location is a main memory accessed through a memory interface.

Claim 15. (original): The circuit of claim 12 wherein said arithmetic logic unit modifies the first exponent by subtracting the contents of said temporary location from said first exponent.

Claim 16. (original): The circuit of claim 12, wherein I is equal to 3.

Docket No.: M4065.0433/P433

Claim 17. (currently amended): A massively parallel processing system, comprising: a main memory;

an array of processing elements, each processing element of the array being coupled to said main memory and other processing elements of said array, wherein each of said processing elements comprises,

a first register block, said first register block including at least one first register for holding a first exponent and a first <u>significant</u> significand of a first floating point number and a first logic capable of left shifting the <u>significant</u> significand of the first floating point number;

a second register block, said second register block including at least one second register for holding a second exponent and a second <u>significant</u> significand of a second floating point number;

a plurality of flags, coupled to said first register block, each of said plurality of flags having a state based on the contents of said first significant; significant;

an arithmetic logic unit coupled to said first register block, said second register block, and said plurality of flags, said arithmetic logic unit causing the first logic to left shift the first significant significand based upon the states of said plurality of flags.

Claim 18. (currently amended): The massively parallel processing system of claim 17, wherein said plurality of flags further comprises:

Docket No.: M4065.0433/P433

an Ith flag, wherein I is a non-negative integer, said Ith flag which is set to a first sate when the 2^I most significant bits of said first <u>significant</u> are each zeros and a second state if any of the 2^I most significant bits is non-zero.

Claim 19. (currently amended): The massively parallel processing system of claim 18, wherein said arithmetic logic unit causes said first logic to left shift by 2^I bits the first significant significand if said Ith flag is set to the first state.

Claim 20. (original): The massively parallel processing system of claim 19, wherein said arithmetic logic unit is coupled to a temporary storage location for storing an adjustment to be subtracted from said first exponent, and increments said adjustment by 2¹ if said first flag is set to the first state.

Claim 21. (original): The massively parallel processing system of claim 18, wherein I is 0.

Claim 22. (original): The massively parallel processing system of claim 18, wherein I is 1.

Claim 23. (original): The massively parallel processing system of claim 18, wherein I is 2.

Docket No.: M4065.0433/P433

Claim 24. (original): The massively parallel processing system of claim 18, wherein I is 3.

Claim 25. (original): The massively parallel processing system of claim 17, wherein said arithmetic logic unit is coupled to a temporary storage location.

Claim 26. (original): The massively parallel processing system of claim 25, wherein said temporary storage location is a register in a register file.

C/

Claim 27. (original): The massively parallel processing system of claim 25, wherein said temporary storage location is a main memory accessed through a memory interface.

Claim 28. (currently amended): The massively parallel processing system of claim 17, wherein:

said plurality of flags further comprises,

an Ith flag, wherein I is a positive integer of at least 3, which is set to a first state when the 2^I most significant bits of said first <u>significant</u> are each zeros and a

Docket No.: M4065.0433/P433

second state if any of the 2¹ most significant bits of said first <u>significant</u> significant is non-zero;

a (I-1)th flag which is set to a first state when the 2^(I-1) most significant bits of said first significant significand are each zeros and a second state if any of the 2^(I-1) most significant bits of said first significant significand is non-zero;

a (I-2)th flag which is set to a first state when the 2^(I-2) most significant bits of said first significant significand are each zeros and a second state if any of the 2^(I-2) most significant bits of said first significant significand is non-zero; and

a (I-3)th flag which is set to a first state when the 2^(I-3) most significant bits of said first significant significand are each zeros and a second state if the 2^(I-3) significant bits of said first significant significand is non-zero; and wherein

said arithmetic logic unit is coupled to a temporary storage location, said arithmetic logic unit initially setting the temporary storage location to zero, then modifying said temporary location based upon the state of the plurality of flags, and finally modifying said first exponent based on the contents of said temporary location.

Claim 29. (original): The massively parallel processing system of claim 28, wherein said temporary storage location is a register in a register file.

Claim 30. (original): The massively parallel processing system of claim 28, wherein said temporary storage location is a main memory accessed through a memory interface.

Docket No.: M4065.0433/P433

Claim 31. (original): The massively parallel processing system of claim 17 wherein said arithmetic logic unit modifies the first exponent by subtracting the contents of said temporary location from said first exponent.

Claim 32. (original): The massively parallel processing system of claim 18, wherein I is equal to 3.

Claim 33. (currently amended): A method for normalizing the <u>significant significand</u> of a floating point number stored in a processing element having an exponent register, a plurality of <u>significant significand</u> registers, an Ith flag indicating whether the 2^I most significant bits of the <u>significant significand</u> are each zero, a (I-1)th flag indicating whether the 2^I most significant bits of the <u>significand</u> are each zero, a (I-2)th flag indicating whether the 2^(I-2) most significant bits of the <u>significand</u> are each zero, a (I-3)th flag indicating whether the 2^(I-3) most significant bit of the <u>significant significant</u> significant bits of the <u>significant significant</u> significant significan

- (a) initializing the temporary variable to zero;
- (b) if said Ith flag is set, left shifting the <u>significant</u> significand by 2^I bits and incrementing the temporary variable by 2^I;
- (c) if said (I-1)th flag is set, left shifting the <u>significant</u> significand by 2^(I-1) bits and incrementing the temporary variable by 2^(I-1);

Docket No.: M4065.0433/P433

(d) if said (I-2)th flag is set, left shifting the <u>significant</u> significand by 2^(I-2) bits and incrementing the temporary variable by 2^(I-2);

(e) if said (I-3)th flag is set, left shifting the <u>significant</u> significand by $2^{(I+3)}$ bit and incrementing the temporary variable by $2^{(I-3)}$; and

(f) decrementing the exponent register by the value of the temporary variable.


Claim 34. (original): The method of claim 33, wherein I is equal to 3.

Claim 35. (original): The method of claim 33, wherein step (a) is performed before step (b).

Claim 36. (currently amended): The method of claim 33, 43, wherein step (c) is performed after step (b).

Claim 37. (currently amended): The method of claim 34, 44, wherein step (d) is performed after step (c).

Claim 38. (currently amended): The method of claim <u>35</u>, 45, wherein step (e) is performed after step (d).



Docket No.: M4065.0433/P433

Claim 39. (currently amended): The method of claim <u>36</u>, <u>46</u>, wherein step (f) is performed after step (e).